BEST AVAILABLE COPY



## **EXCAVATION WALL CONSTRUCTION METHOD**

Patent number:

JP2000297590

Publication date:

2000-10-24

Inventor:

SUZUKI SHIGETAKA

Applicant:

CHEM GROUTING CO LTD

Classification:

International;

E21D5/00; E02D17/04; E21D1/03

- european;

Application number:


JP19990108860 19990416

Priority number(s):.

## Abstract of JP2000297590

PROBLEM TO BE SOLVED: To provide an excavation wall construction method requiring no earth retaining timbering for performing construction or reconstruction in a narrow space and for lowering a construction time and a construction cost.

SOLUTION: This excavation wall construction method includes the following processes; an excavating building process in which a plurality of box column row walls 5 connecting working box column walls 3 installed in the four corners to each other are arranged and built in predetermined positions, a PC steel wire inserting process in which a plurality of PC steel wires 7 are curved arouately so as to be inserted for penetrating the continuously built working box column walls 3 and the box column row walls 5, a PC steel wire straining process in which both ends in each of the PC steel wires 7 are pulled so as to be fixed to the working box column walls 3, a column wall inside concrete placing process in which concrete is charged and placed in all the working box column walls 3 and the box column row walls 5, and a shaft excavating process in which the inside of the excavation wall is dug for forming a space.



Data supplied from the esp@cenet database - Patent Abstracts of Japan

# BEST AVAILABLE COPY

(19)日本国特許庁(JP)

(12) 公開特許公報(A)

(11)特許出版公览番号 特 關 2000 — 297590

(P2000-297590A)

(43)公開日 平成12年10月24日(2000.10.24)

(5!) Int.Cl.'	•	酸別記号	FI		Ŷ <b>~</b> ₹73 <b>~\* (参考</b> )
E21D	5/00		E 2 1 D	<b>B/00</b>	
E02D	17/04	•	E 0 2 D	17/04	E
E 2 1 D	1/03		E 2 1 D	1/03	

#### 審査請求 未請求 請求項の数5 〇L (会 7 頁)

#### (54) 【発明の名称】 掘削壁築造工法

### (57)【要約】

【課題】 狭い場所での工事及び再工事が可能でかつ、 工事時間とコストの低減を図る山留め支保工不要の提削 壁禁造工法の提供。

【解決手段】 4隅に設置する作業用箱型柱盤(3)とその作業用箱型柱壁(3)間を連設する複数の箱型柱列盤(5)を所定の位置に配列して建て込む掘削建込み工程と、建て込み連設された作業用箱型柱壁(3)と箱型柱列壁(5)とを複数のPC網線(7)を円弧状に湾曲させて串刺し状に排入するPC網線押入工程と、その複数のPC網線(7)のそれぞれの両端を引張って作業用箱型柱盤(1)に定着させるPC網線緊張工程と、全作業用箱型柱盤(3)及び箱型柱列壁(5)にコンクリートを充填打設する柱壁内コンクリート打設工程と、据削壁の内部を掘削して空間を造成する立坑掘削工程、とを含んでいる。

